

## C-SERIES



Ideal for heavy duty commercial environments

Suitable for truck stop, marina and airfield

Available in mono or twin

Petrol, Diesel, Gas Oil, Avgas and Jet A1

W&M, ATEX, DMG14 and MID approved

0.2% meter accuracy

Four speed options

Stainless steel construction

Range of interface options

Use with above and below-ground tanks

## C Series Commercial

ATEX, MID & W&M Approved for the Resale of Fuel

C-Series Commercial pumps and dispensers provide the ultimate in commercial fuelling equipment for heavy duty environments where speed of fuelling and reliability is vital. From large fleet garages, truck stops, marinas or small air fields, the C Series Commercial range provides a robust, accurate and visually attractive fuelling solution.

All C-Series pumps are built to the highest specification from long-lasting stainless steel and incorporate the latest technology. These C-Series Commercial pumps are available in either mono or twin models, and in four speeds – 45, 70, 90 and 180 LPM.

Low-cost, long-term cost of ownership is an integral consideration in the design of the C-Series range as is speed of fuelling and reliability – vital to commercial fuel operators.



## C-Series Commercial

ATEX, MID & W&M Approved for the Resale of Fuel

### Specification

- › Single-sided 25mm illuminated digital commercial displays (volume only)
- › Available as mono or twin
- › Pumping unit with integral air separation (not included in dispenser format)
- › 0.2% meter accuracy
- › Solenoid valve
- › Elaflex 3.3m hoses (black as standard)
- › Approved 'latch open' nozzles with safety break
- › Infra-red management control
- › Stainless steel construction
- › Single or three-phase motors (115v/230v/380v)
- › Integral nozzle locking (no padlocks required)
- › Interface options include Pulse, Serial, Gilbarco 2 Wire and HL2
- › Manufactured to EN13617-1 SIRA Certificate number 05ATEX9095
- › Approved by UK Weights & Measures (attendant operated or fuel monitoring system)
- › Measuring Instrument Directive approved
- › Ministry of Defence Design and Maintenance Guide 14 (DMG14)
- › 12 months warranty

### Options

- › Second side display
- › Stainless steel under-pump plinth
- › Galvanised under-pump stool
- › GRP under-pump sump
- › Built-in hose retriever
- › High hose option
- › Standard outlet
- › Inline safety breaks ¾" – 1"
- › Stage Two vapour recovery
- › Marine grade stainless steel panels available
- › Aviation hoses available
- › Avgas suitable conversions available
- › Front-loading nozzle (mono only)

### Dimensions

- › Mono: 1425mm (H) x 370mm (W) x 450mm (D) – Weight: 84kg
- › Twin: 1425mm (H) x 540mm (W) x 450mm (D) – Weight: 140kg

### Checklist

- ✓ Approved for Re-sale
- ✓ Petroleum & Diesel
- ✓ Alternative Fuel
- ✓ Electronic